

MASTERSEAL[®] BLOW HOLE FILLER

Quick drying, ready-mixed blow hole filler

Description

MASTERSEAL[®] BLOW HOLE FILLER is a ready-mixed, pre-bagged blend of acrylic polymers and graded fillers for re-levelling and refurbishment of most building surfaces prior to over coating.

Advantages

- Easy to apply.
- Does not flake off or de-laminate.
- Good adhesion.
- Minimal shrinkage
- Quick drying.
- Vapour permeable.
- White in colour.
- Non-toxic.

Area of use

When dry, MASTERSEAL[®] BLOW HOLE FILLER bonds extremely well to cementitious materials, gypsum, gypsum boards, spray plasters and wood.

Packaging

MASTERSEAL[®] BLOW HOLE FILLER is supplied in 25kg units.

Preparation of surface

Ensure that the surface is free from dust, dirt, form oil and contamination. Ridges and undulations must also be removed.

N.B. The use of penetrating primer is recommended on dusting or flaking surfaces, for further information contact BASF UAE Technical Department.

Coverage

Apply the filler in a thin even layer between 0.2-0.4kg/m² (dependent on substrate conditions), diluting with water as required. Apply two coats if necessary, allowing to dry between layers. Lightly sand down the final surface before overcoating within 24 hours of application. Total applied material must not exceed 1mm

Storage

Store containers in a clean dry area protection from direct sunlight and extreme heat and cold.

Health and Safety

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.

Note

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF representative.

BASF reserves the right to have the true cause of any difficulty determined by accepted test methods.

Quality and care

All products originating from BASF's Dubai, UAE facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001, ISO 14001 and OHSAS 18001.

02/2005 BASF_CC-UAE revised 08/2005

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

As all BASF technical datasheets are updated on a regular basis it is the user's responsibility to obtain the most recent issue.